

DECLARATION OF PERFORMANCE
according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014
for WEBAC® PURseal M SL10

No.: PURsealMSL10-01

Unique identification code of the product-type:
WEBAC® PURsealMSL10 EN 13813:2002 SR – B1.5

Intended use/es:

Resin screed

Manufacturer:

WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany

System/s of AVCP:

system 4

Harmonised standard:

EN 13813:2002

Notified body/ies:

Irrelevant

WEBAC®

WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

Declared performance/s:

essential characteristics	performance	system of assessment and verification of constancy of performance	harmonised technical specification
Fire behavior	E _{fl}	system 4	EN 13813: 2002
Release of corrosive substances	SR		
Water permeability	NPD		
Abrasion resistance	NPD		
Bond strength	B 1.5		
Impact strength	NPD		
Acoustic insulation	NPD		
Sound absorption	NPD		
Thermal insulation	NPD		
Chemical resistance	NPD		

Appropriate Technical Documentation and / or Specific Technical Documentation:

Performance without additional testing: fire class E_{fl}

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Meik Weickenmeier – General Manager

Barsbüttel, September 9, 2019

(signature)

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data Sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is attached to this Declaration of Performance.



WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

CE marking label for WEBAC® PURseal M SL10:



WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel

19

PURsealMSL10-01

EN 13813 : 2002

Synthetic resin

EN 13813:2002 SR – B1.5

Fire behavior: E_{fl}

Release of corrosive substances: SR

Bond strength: B1.5